



# HAND CUTTING TORCH

## 7505 - "M" TYPE CUTTING TORCH

### SPECIFICATIONS

Cutting Capacity : 1mm - 30mm (1/32" - 1 1/4")

Torch Connection : 3/8" BSP



K417/022

### CUTTING NOZZLE

| PART NO. | NOZZLE SIZE | ORIFICE m/m | CUTTING RANGE m/m | OXY. PRESSURE | ACETYL. PRESSURE |
|----------|-------------|-------------|-------------------|---------------|------------------|
| K417/250 | M 1         | 0.7         | 1 - 5             | 2.5           | 0.3              |
| K417/251 | M 2         | 0.9         | 5 - 15            | 3.0           | 0.3              |
| K417/252 | M 3         | 1.1         | 15 - 30           | 3.5           | 0.3              |

## 1601 BS CUTTING TORCH

A heavy duty cutting torch, design to assure operator comfort after hours of continuous cutting.

### FEATURES

Cutting Capacity : 300mm

Stainless steel gas tubes for greater heat resistance.

Top stainless steel lever with latch for heavy cutting

Die forged brass head for added strength and durability.



K417/001

### APPLICATIONS

For heavy cutting, heating, rivet cutting and washing, gouging.

### SPECIFICATIONS

| PART NO. | HEAD | LENGTH |
|----------|------|--------|
| K417/000 | 75°  | 500mm  |
| K417/001 | 90°  | 500mm  |
| K417/002 | 180° | 500mm  |
| K417/003 | 75°  | 1000mm |
| K417/004 | 90°  | 1000mm |

| PART NO. | HEAD       | LENGTH |
|----------|------------|--------|
| K417/005 | 180°       | 1000mm |
| K417/006 | 75/90/180° | 1500mm |
| K417/007 | 75/90/180° | 1850mm |
| K417/008 | 75/90/180° | 2000mm |

## 1602 JIS CUTTING TORCH

A medium duty cutting torch, design to assure operator comfort after hours of continuous cutting.

### FEATURES

\* Cutting Capacity : 300mm

\* Stainless steel gas tubes for greater heat resistance.

\* Top stainless steel lever

\* Die forged brass head for added strength and durability.

### APPLICATIONS

\* For cutting, heating, rivet cutting and washing, gouging.

### SPECIFICATIONS

| PART NO. | HEAD | LENGTH |
|----------|------|--------|
| K417/011 | 90°  | 500mm  |



K417/011