



BENCH DRYING OVEN



A HIGHLY RELIABLE HOLDING, REBAKING AND RECONDITIONING ELECTRODE OVEN OF MILD STEEL INNER CASING. STURDILY CONSTRUCTED FOR MAXIMUM PERFORMANCE AND CONVENIENCE FOR GOOD QUALITY WELDING.

BENCH TYPE

Capacity – 150 kgs

Electrodes – 457 mm

- **Dries off moisture**
- **Guard against rejects**
- **Eliminate rework**
- **Protect welding profits**

- **Removable shelving for use with flux and wire coils**
- **Even Heat Distribution – circular shape distributes heat by convection**

Specifications :-

Model	KE150-MS
Electrode Capacity	150 KG x 450 MM
Electrode Size	25.4 to 45.7cm also accomodates wire rolls
Heating Elements (2)	1400 watts total
Voltage	240 / 420V AC single phase 50 or 60 cycles
Temperature Range & Control	50°C - 350°C adjustable thermostat control with pilot light
Insulation	2" (5cm) Glass Fiber Batt
Inside Diameter	45.7 cm x 48.2 cm
Shelved Compartments	6 (removable for wire rolls)
Exterior Dimensions	75 x 57 x 58 cm
Weight	57 kgs



A chimney effect that drives air upward along the center support bar, together with the oven's circular shape and vented